

# THE EAGLE HAS LANDED

Set your worries free and glide into the performance and durability of the Alamo Industrial® Eagle 15™ Flex-wing Rotary Mower. Higher rated horsepower gearboxes, a thick deck design, and improved blade tip speeds now offer you the power to cut up to 3-1/2" diameter grass, weeds and brush. Cover more area in less time, all with the trust of an established brand behind you.



## EAGLE 15™

**ALAMO**  
INDUSTRIAL

Eagle 15™

**BUILT SHARPER™**

# Eagle 15™

## Convenient Mount

Attached to the tractor using a level-lift drawbar hitch design, the unit is easily and conveniently mounted. A jack stand comes standard for proper storage of the unit when not in use as well as a safety tow chain.

## Superior Power

The main driveline is CAT 5 constant velocity with CAT 5 wing drivelines featured with slip clutch protection against heavy shock loading.

A 235 HP divider coupled with 205 HP center and wing gearboxes provide the power you need to get through heavily vegetated areas with reliability. Routine maintenance is a snap with newly designed dipsticks featured on the wing gearboxes.

## Safety In Mind

Standard double-row chainguards provide 2-layers of protection to help prevent material from being thrown out from under the machine.

## Durable Tires

Replaceable, puncture resistant, foam-filled airplane tires provide reliable movement of the unit and contribute to steady transport.

## Safely Transported

The unit may be moved down any standard road with ease with its 96" transport width. A newly designed safety lock is featured for additional protection during highway transport.



## Optimal Cutting Performance

A reinforced heavy duty steel pan blade carrier features (2) free-swinging 1/2" x 4" updraft blades capable of cutting up to 3-1/2" diameter grass, weeds and brush. Blade tip speeds have been increased now performing at a minimal 16,286 FPM, which translates into better cutting performance for you.

A standard deck ring incorporates a round rolled flat bar ring welded to the underside of the deck preventing the blades from contacting the deck.



Replaceable skid shoes help protect the mower from damaging ground contact.

## Rugged Construction

An easy-clean 7-gauge deck made of heavy-duty steel and 1/4" x 10-1/2" replaceable, bolt-on side skirts promote durability and longer mower life.

## Level and Adjustment

A hydro-mechanical level lift system is featured for a uniform cut. The mower cutting height may be adjusted from 1/2" to 14-1/2" for your specific application. A spring-cushioned axle absorbs shock when unit is in motion.

## Additional Options

- Open or Closed Center
- Three-Spool Valve
- Valve Mounting Kit
- Winch & Stand
- Auxiliary Wheel Spindle Kit
- Special Paint

This information is intended to be of a general nature only; specifications are subject to change without notice as we continue to improve our products.

© 2004 Alamo Group Inc. Alamo Industrial is a registered trademark of Alamo Group Inc.



## Additional Specifications

**Overall Width:**  
186"  
**Overall Length:**  
183"  
**Minimum Tractor HP Requirements:**  
50 HP  
**Gearbox Rating:**  
Power Divider – 235 HP  
Center & Wings – 205 HP

**Blade Tip Speed:**  
Center  
540 RPM – 16,286 RPM  
1,000 RPM – 16,380 RPM  
Wings  
540 RPM – 16,415 RPM  
1,000 RPM – 17,137 RPM  
**Output Shaft Diameter:**  
2-3/8"  
**Unit Shipping Weight:**  
5,695 lbs. (Approx)

**Warranty:** The mower itself features a minimum one year parts and labor. The gearboxes feature a 5 year limited warranty. Non-governmental users are subject to a modified policy. Only genuine Alamo Industrial parts may be used for warranty replacement.

1,500/1204/WM

**ALAMO**  
INDUSTRIAL  
**BUILT SHARPER™**

1502 East Walnut St. • Seguin, Texas 78155

1-800-882-5762

www.alamo-industrial.com