

THE EAGLE HAS LANDED

Set your worries free and glide into the performance and durability of the Alamo Industrial® Eagle 15™ Flex-wing Rotary Mower. Higher rated horsepower gearboxes, a thick deck design, and improved blade tip speeds now offer you the power to cut up to 3-1/2" diameter grass, weeds and brush. Cover more area in less time, all with the trust of an established brand behind you.



EAGLE 15™

ALAMO
INDUSTRIAL

Eagle 15™

BUILT SHARPER™

Eagle 15™

Convenient Mount

Attached to the tractor using a level-lift drawbar hitch design, the unit is easily and conveniently mounted. A jack stand comes standard for proper storage of the unit when not in use as well as a safety tow chain.

Safety In Mind

Standard double-row chainguards provide 2-layers of protection to help prevent material from being thrown out from under the machine.

Durable Tires

Replaceable, puncture resistant, foam-filled airplane tires provide reliable movement of the unit and contribute to steady transport.

Safely Transported

The unit may be moved down any standard road with ease with its 96" transport width. A newly designed safety lock is featured for additional protection during highway transport.

Superior Power

The main driveline is CAT 5 constant velocity with CAT 5 wing drivelines featured with slip clutch protection against heavy shock loading.

A 235 HP divider coupled with 205 HP center and wing gearboxes provide the power you need to get through heavily vegetated areas with reliability. Routine maintenance is a snap with newly designed dipsticks featured on the wing gearboxes.



Optimal Cutting Performance

A reinforced heavy duty steel pan blade carrier features (2) free-swinging 1/2" x 4" updraft blades capable of cutting up to 3-1/2" diameter grass, weeds and brush. Blade tip speeds have been increased now performing at a minimal 16,286 FPM, which translates into better cutting performance for you.

A standard deck ring incorporates a round rolled flat bar ring welded to the underside of the deck preventing the blades from contacting the deck.



Replaceable skid shoes help protect the mower from damaging ground contact.

Rugged Construction

An easy-clean 7-gauge deck made of heavy-duty steel and 1/4" x 10-1/2" replaceable, bolt-on side skirts promote durability and longer mower life.

Level and Adjustment

A hydro-mechanical level lift system is featured for a uniform cut. The mower cutting height may be adjusted from 1/2" to 14-1/2" for your specific application. A spring-cushioned axle absorbs shock when unit is in motion.

Additional Options

- Open or Closed Center Three-Spool Valve
- Valve Mounting Kit
- Winch & Stand
- Auxiliary Wheel Spindle Kit
- Special Paint

This information is intended to be of a general nature only; specifications are subject to change without notice as we continue to improve our products.

© 2004 Alamo Group Inc. Alamo Industrial is a registered trademark of Alamo Group Inc.



Additional Specifications

Overall Width:
186"
Overall Length:
183"
Minimum Tractor HP Requirements:
50 HP
Gearbox Rating:
Power Divider – 235 HP
Center & Wings – 205 HP

Blade Tip Speed:
Center
540 RPM – 16,286 RPM
1,000 RPM – 16,380 RPM
Wings
540 RPM – 16,415 RPM
1,000 RPM – 17,137 RPM
Output Shaft Diameter:
2-3/8"
Unit Shipping Weight:
5,695 lbs. (Approx)



1502 East Walnut St. • Seguin, Texas 78155

1-800-882-5762

www.alamo-industrial.com

Warranty: The mower itself features a minimum one year parts and labor. The gearboxes feature a 5 year limited warranty. Non-governmental users are subject to a modified policy. Only genuine Alamo Industrial parts may be used for warranty replacement.