

# FALCON 15™

# Rotary Mowers

# HYDRAULIC POWER MEETS MECHANICAL STRENGTH



Unruly vegetation is no match for the hydraulic Falcon™ Flex-Wing rotary mower. Its strength, power and safety features such as automatic shutoff that stops the blades from spinning when the wings are elevated make it one of the most advanced mowers on the market. With the Falcon, you have the flexibility to engage the side of the mower you need without posing the danger of exposed spinning blades to your operators or bystanders. This makes this hydraulic flex-wing perfect for hunting down overgrown vegetation on expansive spaces like medians and right of ways as well as airports, parks and school grounds.

# FALCON 15™

**ALAMO**  
INDUSTRIAL  
**BUILT SHARPER™**

# Falcon 15™

Designed for optimum performance and safety, the Falcon™ mows cutting paths ranging from 10' to 15'. This hydraulic flex-wing incorporates safety features such as no moving parts on the top deck and automatic blade shutoff when the wing is lifted.

## Hydraulic Power

Power for the unit is provided by three hydraulic gear-type motors with a high capacity 35-gallon tank. The motor control electrical circuit utilizes environmentally sealed Weather-Pack and Metri-Pack wire connectors to withstand harsh mowing environments.

## Rugged Construction

The Falcon shares the same rugged mower chassis as the field-proven mechanical Eagle™ Flex-Wing. The unit is continuously welded to enhance strength and durability for rough municipal mowing.

## Safety In Mind

Standard double-row chainguards provide 2-layers of protection to help prevent material from being thrown out from under the machine.

## Choose Your Width

The Falcon 15' is also available in a 10' version which is exactly the same base model excluding the left wing.

## Optimal Visibility

The operator has the ability to view site gauges from inside the tractor cab for continuous monitoring of hydraulic filter condition, fluid level and fluid temperature.

## Mount

The Falcon mounts to tractors with a minimum 50 PTO HP and features a self-level lift drawbar hitch design for uniform cutting.

## Easily Replaceable Parts

Bolt-on side skirts provide ease of maintenance and replaceable skid shoes help protect the mower from damaging ground contact.

## Productivity Includes Safety

The blades will cut 3-1/2" diameter grass and weeds. A deck ring prevents the blades from contacting the top deck. For safety with productivity in mind, an automatic shutoff system engages individually on either wing when lifted above 45° from the ground allowing for productivity in small spaces without the hazard of exposed spinning blades.

This information is intended to be of a general nature only; specifications are subject to change without notice as we continue to improve our products.

© 2008 Alamo Group Inc. Alamo Industrial, Boom-Axe, Flail-Axe, BuzzBar, Quick Hitch and Falcon15 are registered trademarks of Alamo Group Inc.

MEMBER OF THE  
ALAMO GROUP  
ALWAYS ON THE CUTTING EDGE™

## Additional Specifications

Overall Width: 186"  
Overall Length: 183"  
Overall Height: 85-1/2"  
Overall Transport Width: 96"  
Overall Cutting Width: 180"  
Cutting Capacity: 3-1/2" material  
Unit Shipping Weight: 5,420 lbs.

Warranty: Minimum one year parts and labor.  
Non-governmental users are subject to a modified policy.  
Only genuine Alamo Industrial parts may be used for warranty replacement.

5,000/308/WM

**ALAMO**  
INDUSTRIAL  
**BUILT SHARPER™**

1502 East Walnut St. • Seguin, Texas 78155

1-800-882-5762

www.alamo-industrial.com