

SR620

Flex-Wing Rotary Mower - Cutting Width 6.2m (20' 3")

Machine Features

- » 6.20m (20' 3") Cutting width
- » Heavy Duty gearboxes
- » 5 Rotor configuration
- » Slip clutch protection
- » 1000rpm wide angle PTO
- » Hardened updraft swinging blades
- » Walking Axles
- » 115° Wing movement
- » Anti-scalp discs



Multi-blade Option

Improves mulching thanks to the six blade configuration; 3 up-draft blades first cut and then push the crop in to the path of a further 3 shredder blades for complete mulching.



Description		SR620
Cutting width	Maximum width of cut (m)	6.20 (20' 3")
HP requirement	Maximum HP requirement of tractor	90
Weight	Weight of machine (kg)	2512
Cutting height	Minimum to maximum cutting height (mm)	25-400
Cutting capacity	Maximum diameter of material to be cut (mm)	50
Overall width	Maximum external width (m)	6.40
Overall length	Maximum external length (m)	4.85
Transport width	Width when folded for transport (m)	2.80
Transport height	Height when folded for transport (m)	2.60
PTO speed	Maximum RPM of PTO shaft	1000
Gearbox rating	Power divider (hp)	170
	Rotor gearbox (hp)	111
Slip clutch protection	Number of slip clutch protection	5
Number of blades	The number of heat treated updraft blades	15
Blade tip speed	Wings (measured in meters per min)	5340
Rotor speed	Wings (measured in m per min)	5340
Blade overlap (mm)	Distance blades overlap when running (mm)	110
Hydraulic wing flex	Degrees of wing travel in work	90° up / 25° down
Wheels	Number of wheels	8
Skid Shoes	Replaceable skid shoes	Standard