

ROTARY MOWER

5R420

SR420 - 4.20m (13'9") working width

SR SERIES	
MODEL	SR420
Specification	
Working width	4.20m (13'9")
Cutting height	10mm-400mm
Cutting capacity	50mm
Tractor requirement & attachment	
HP requirement	70
Method of attachment	3-point linkage
Dimensions	
Weight	1700kg
Overall width	4.4m
Overall length	3.0m
Transport width	2.8m
Transport height	2.0m
Equipment details	
PTO speed	1,000rpm
Protection	Slip clutch
Number of blades	6
Number of rotors	3
Blade overlap	110mm
Blade tip speed	4800m/min
Hydraulic wing flex	45° up, 12° down
Wheels	4



HIGH-PERFORMANCE FLEX-WING TECHNOLOGY

The SR420 is 3-point linkage mounted and slightly more manoeuvrable than the SR15. It also features anti-scalp discs, a floating linkage system, deck protection rings and a wider choice of cutting heights.

Designed for productivity with three high-performance rotors and six cutting blades, the SR420's hardened updraft swinging blades ensure an effective cutting capacity of up to 50mm, while hydraulically folding wings enable a fast and smooth transition from transport to working position.

KEY FEATURES

Ideal for large-scale farmers, local government teams, and professional mowing contractors, SR series machines can be used in a huge variety of applications from airports and sports venues to pasture and stubble.

- 4.2m working widths
- Floating linkage system
- 57 degrees of wing movement (+45° up, -12° down)
- Heavy-duty gearboxes
- 1000rpm wide angle PTO
- Slip clutch protection
- Front and rear chain guards
- Hardened updraft swinging blades
- Cutting heights from 10m to 400mm
- 50mm cutting capacity
- Six blades
- Overlapping blades
- Low tractor hp requirement (70hp)



