

PI



SR620 - 6.20m (20'4") working width

MODEL	SR620
Specification	
Working width	6.20m (20'4")
Cutting height	25mm-400mm
Cutting capacity	50mm
Tractor requirement & attachment	
HP requirement	90
Method of attachment	Drawbar
Dimensions	
Weight	2512kg
Overall width	6.4m
Overall length	4.85m
Transport width	2.8m
Transport height	2.6m
Equipment details	
PTO speed	1,000rpm
Protection	Slip clutch
Number of blades	10, 15, 20 or 30
Number of rotors	5
Blade overlap	110mm
Blade tip speed	5340m/min
Hydraulic wing flex	90° up, 25° down

Wheels



8

OUTSTANDING PRODUCTIVITY

McConnel's high-performance SR620 features a 6.2m cutting width, five powerful rotors and a choice of 10 to 30 hardened updraft swinging blades for outstanding productivity.

Capable of tackling everything from grass to gorse, the SR620 can cut material up to 50mm thick, and has a fast-cutting action for outstanding productivity. 115 degrees of wing movement ensure the SR620 closely follows the contours of the ground and delivers an attractive cut with an even spread, while walking axles deliver a smoother ride.





KEY FEATURES

Ideal for large-scale farmers, local government teams, and professional mowing contractors, SR machines can be used in a huge variety of applications from airports and sports venues to pasture and stubble.

- 6.2m working width
- High and low hitch options
- 115 degrees of wing movement (+90° up, -25° down)
- Bondioli & Pavesi gearboxes and drivelines
- Five powerful rotors
- 1000rpm wide angle PTO
- Slip Clutch Protection
- Front and rear chain guards
- Hardened updraft swinging blades
- Cutting heights from 25mm to 400mm
- 50mm cutting capacity
- Choice of 10, 15, 20 or 30 blades
- Walking axles